

ELECTRIC ORDER PICKER

The EKKO Electric Order Picker is designed for safe and efficient order picking at height. With a compact footprint, smooth electric drive, and sturdy construction, it is ideal for warehouses, distribution centers, and retail environments.



★ KEY FEATURES

- ✓ Proportional Lift & Drive Control
- ✓ Emergency Lowering System
- ✓ Non-Marking Tires
- ✓ Onboard Charger
- ✓ Fault Diagnosis System
- ✓ Tilt Sensor with Alarm
- ✓ Load Sensing System
- ✓ Platform Self-Lock Gate
- ✓ Emergency Stop Button

SPECIFICATIONS

MODEL	EOPH15 -118	EOPH15 -157	EOPH15-196
Maximum Platform Height	118 in	157 in	196 in
Overall Length	162 in	202 in	202 in
Overall Width	30 in	30 in	30 in
Overall Height	58 in	71 in	71 in
Platform Size (LxW)	27 x 28 in	27 x 28 in	27 x 28 in
Extension Deck Size (LxW)	22 x 29 in	22 x 29 in	22 x 29 in
Ground Clearance	2.4 in	2.4 in	2.4 in
Wheelbase	48 in	48 in	48 in
Turning Radius (Outside)	67 in	67 in	67 in
Load Capacity	330 lb	330 lb	330 lb
Platform Capacity	200 lb	200 lb	200 lb
Drive Motor	24V / 0.50 HP	24V / 0.50 HP	24V / 0.50 HP
Lift Motor	24V / 1.00 HP	24V / 1.00 HP	24V / 1.00 HP
Travel Speed (Lowered)	0 – 2.5 mph	0 – 2.5 mph	0 – 2.5 mph
Travel Speed (Raised)	0 – 0.6 mph	0 – 0.6 mph	0 – 0.6 mph
Up/Down Speed	20 / 26 sec	25 / 32 sec	25 / 32 sec
Gradeability (Loaded)	5%	5%	5%
Battery	24V / 100Ah	24V / 100Ah	24V / 100Ah
Charger	24V / 15A	24V / 15A	24V / 15A
Service Weight	1,850 lb	1,918 lb	2,100 lb

PERFORMANCE

MODEL	EOPH15 -118	EOPH15 -157	EOPH15-196
Lift Height	118 in	157 in	196 in
Platform Height (Raised)	112 in	150 in	189 in
Platform Height (Lowered)	20 in	20 in	20 in
Front Wheel Size	8 x 2.95 in	8 x 2.95 in	8 x 2.95 in
Rear Wheel Size	6 x 2 in	6 x 2 in	6 x 2 in
Drive Wheel	2	2	2
Brakes	Electromagnetic	Electromagnetic	Electromagnetic
Control System	AC Curtis	AC Curtis	AC Curtis