

LITHIUM ORDER PICKERS

EOP70-Li Series

- 2200 lbs. Capacity
- 196 in. Lift Height
- Auxiliary Lift Forks
- EPS (Electric Power Steering)
- German AC Drive Motor
- Curtis Controller
- Battery and Charger Included
- 3 Year Limited Warranty



EOP Lithium Series

Superior quality, maneuverable, compact, and durable for all your material handling applications. Ideal for narrow aisles and high-level picking.

WEIGHT CAPACITY: 2200 lbs. @ 24" load center

LIFT HEIGHT: 196"

FORK LENGTH: 42.13"

MAST HEIGHT: 98.03"

TURNING RADIUS: 61.81"

BATTERY / CHARGER: 24V/350AH Lithium, 24V/50A Lithium Charger

SPEED TRAVEL: 4.97 mph empty ; 4.97 mph loaded

LIFTING SPEED: 5.35 ips empty; 3.6 ips loaded

LOWERING SPEED: 3.85 ips empty; 4.4 ips loaded

DRIVE WHEELS: 9" x 3" polyurethane

STABILITY: 4" x 2" polyurethane

LOAD WHEELS: (2) 4" x 3" polyurethane per outrigger

HYDRAULICS LIFTING MOTOR: 24V 6000-Watt lifting motor with hardened chrome moly steel for durability.

DRIVE MOTOR: 24V German AC 3000Watt drive motor for efficiency and high torque. Curtis **EPS (Electric Power Steering)**

AC CONTROLLER: 24V CURTIS Instrument provides performance through entire range of speed; Constant travel speed regardless of load; Battery discharge indicator combination gauge.

BRAKES: Electro-magnetic braking for secure stopping power; Electronic neutral braking for accurate control.

OPERATOR CONTROLS: Throttle, lifting, lowering, turtle mode and horn functions are in the ergonomic handle; Offset steering handle to provide better visibility; Belly button reverse safety feature allows the unit to stop and reverse to avoid collision or injury.

CHASSIS AND MAST: Robotic Welding; Heavy duty steel chassis with I-beam mast for durability; Telescoping mast includes a protective steel guard.

Lithium Order Picker

